


USED FOR RESIDENCES, BARNS, PRIVATE GARAGES, ETC.



# **SECTION S-S**

## NOTES:

- The driveway detailed on this sheet shall be used under the following conditions:
  - the mainline shoulder is paved and is less than 8 ft in width
  - the mainline shoulder is not paved
- If the driveway surface is unimproved cross section as for driveway Class V can be used in place of Section S-S, see Drawing E 610-DRIV-11 for details.
- See Standard Drawing E 610-DRIV-07 for General Notes.
- See Standard Drawing E 610-DRIV-06 for Sections A-A and B-B.

## **LEGEND**

- M Limits of HMA for approaches
- P Limits of compacted aggregate base
- S Equivalent to surface in place

#### Width variable

165 #/syd HMA Surface Type A on

275 #/syd HMA Intermediate Type A on
8 in. compacted aggregate base #53

## **HMA FOR APPROACHES**

TYPICAL SECTION

# INDIANA DEPARTMENT OF TRANSPORTATION CLASS II DRIVE MARCH 2003 STANDARD DRAWING NO. E 610-DRIV-04



/s/ Richard L. VanCleave 3-03-03
DESIGN STANDARDS ENGINEER DATE

/s/ Richard K.Smutzer 3-03-03 CHIEF HIGHWAY ENGINEER DATE